

Product Highlights

- Operating temperature up to +150°C (+302°F)
- Excellent noise suppression
- Uniform appearance
- Abrasion resistant
- Extremely lightweight
- Does not trap heat or moisture

Typical Applications

- Instrument panel harnesses
- Body wiring harnesses
- Dome light wiring harnesses
- Door lock rods
- Tubing, hose, and cable assemblies



QuietSleeve® 3410 is a highly flexible and expandable sleeve used to suppress noise on wires and cable assemblies. Its rugged construction also provides abrasion protection that is superior to foam.

QuietSleeve 3410 is easy to apply with one size accommodating a variety of applications. In addition, the open weave construction permits drainage and prevents condensation.

QuietSleeve 3410 is a braided from a combination of monofilament, polyester abrasion-resistant strands and multifilament, polyester, noise suppression strands.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data – QuietSleeve® 3410

Property	Test Method	Result
Temperature Rating	240 hours at +175°C (+150°C rating)	Pass +150°C (+302°F)
Low Temperature Flexibility	SAE J2192	Pass -40C (-40F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	SAE J2192	Pass
Noise Suppression	SAE J2192	Rubbing: > 15dB Rattling: > 25dB

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Construction and Typical Product Characteristics

Resilient Support Yarn: Polyester (PET) monofilament

Noise Suppression Yarn: Polyester (PET) multifilament

Standard Sizes

Commercial Product Name	Nominal size (mm)
QuietSleeve 3410 3	3
QuietSleeve 3410 6	6
QuietSleeve 3410 13	13
QuietSleeve 3410 19	19
QuietSleeve 3410 25	25
QuietSleeve 3410 32	32

Availability

Standard sizes are listed here. Additional sizes could be available upon request.

Available in spools and custom cut lengths. Recommended cut lengths are in 5mm increments. Please see regional drawing for cut length tolerances.

Standard color is black. Additional colors may be available.

Please consult your local sales representative for regional packaging details and standards.



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600
EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560
Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565
www.tennecosp.com



For informational purposes only. Tenneco makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. Tenneco's only obligations are those provided in its terms and conditions of sale for this product, and Tenneco will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2020 Tenneco Systems Protection, manufacturer of Bentley-Harris protection products.

QS3410-NA(EN-LTR)A